



ISSN : 2347 - 2243

Indo - American Journal of Life Sciences and Biotechnology



<https://iajlb.org>

Email : editor@iajlb.com or iajlb.editor@gmail.com



Microbial Production of Bioethanol From Agricultural Residues: Pretreatment Strategies and Yield Constraints

Ebba Lindqvist¹●, Daan Verhoeven²●, Maja Ekstrom³●

¹Assistant Professor, Department of Biotechnology, Dalarna Institute of Environmental Biology, Falun, Sweden.

²Professor, Department of Biotechnology, Veluwe Institute of Molecular Biology, Apeldoorn, Netherlands.

³Professor, Department of Biotechnology, Dalarna Institute of Environmental Biology, Falun, Sweden.

Email: ¹e.lindqvist2@dieb.se, ²d.verhoeven@vimb.nl, ³m.ekstrom@dieb.se

ORCID: ¹0000-0001-1899-7281, ²0000-0001-2945-4223, ³0000-0001-1446-0751

Received: February 25, 2016 Accepted: June 7, 2016 Published: September 11, 2016

DOI: [10.62644/iajlb.2016.v12.i3.pp19-28](https://doi.org/10.62644/iajlb.2016.v12.i3.pp19-28)

ABSTRACT

Agricultural residues such as cereal straws and corn stover are abundant, cheap and not directly in competition with food crops, which is why they have attracted so much attention as a raw material for bioethanol. Turning them into fuel is harder than the raw material price suggests. This narrative review looks at how microbial ethanol production from residues works, why pretreatment sits at the centre of the process, and which constraints hold final yield below what the chemistry of the sugars would allow. It draws on published work on lignocellulose structure, pretreatment chemistry, enzymatic hydrolysis, inhibitor formation, and the engineering of yeasts and bacteria that ferment both glucose and xylose, and it reports no new data. The main finding is that no pretreatment is best on every count: each one trades sugar recovery against inhibitor formation, chemical recovery, energy use or cost, and its performance depends on the residue. Yield is lost at every stage, and the losses interact, so improving one step can shift the problem to the next. The review closes with limits of the evidence, notably that results from different residues, loadings and strains are rarely comparable, and with priorities for future work.

Keywords: Bioethanol; Agricultural residues; Lignocellulose; Pretreatment; Fermentation inhibitors; Xylose fermentation; Narrative review

Citation: Lindqvist, Verhoeven and Ekstrom [2016]. Microbial Production of Bioethanol From Agricultural Residues: Pretreatment Strategies and Yield Constraints. *Indo-Am. J. Life Sci. Biotechnol.* 12(3):19-28. DOI: [10.62644/iajlb.2016.v12.i3.pp19-28](https://doi.org/10.62644/iajlb.2016.v12.i3.pp19-28)

Article Class: Review Article

1. Introduction

Ethanol from sugar and starch crops is an old and familiar fuel, but its link to food has long been uncomfortable. When cropland is converted or crops are diverted to fuel, the arguments about food prices and land use follow (1, 2). Agricultural

residues offer a way out of that argument. Straws, stover and husks are left over once the grain has been harvested, they are produced wherever cereals are grown, and global estimates of the ethanol that could in principle be made from them are large (3). That promise explains much of the



research effort of the past two decades (4, 5).

The promise comes with a catch. The sugars in a straw are locked inside a composite of cellulose, hemicellulose and lignin that plants evolved to resist attack, and the resistance is the whole problem (6). Before microbes can ferment anything, the material has to be opened up by pretreatment, then broken down by enzymes, and the resulting sugars have to be fermented by organisms that were not designed for the mixture they are given (7). Every one of these steps leaks yield.

This article is a narrative review of that chain, with a particular eye on pretreatment and on the constraints that cap yield. It does not report original measurements. The title names no particular region or plant, and so no local data are reported; the aim is to draw together what the published literature says in general, up to the date of this issue, and to be candid about where it is thin or hard to compare. Where claims outrun the evidence, the review says so.

2. Literature Review

2.1 Lignocellulose and Why It Resists

Plant cell walls are built from cellulose microfibrils embedded in a matrix of hemicellulose and lignin. Cellulose is a long glucose polymer, much of it tightly packed and crystalline, whereas hemicellulose is a branched polymer of several sugars, with xylose usually the most abundant in cereal straws (8, 9). Lignin is neither a sugar polymer nor fermentable. It binds the other components together, it limits the access of enzymes to cellulose, and it can bind enzymes directly (10, 11).

No single feature explains the resistance. Crystallinity, the surface area available to enzymes, the degree of association between the polymers and the presence of

lignin all play a part, and the weight of each differs between plants and even between tissues of the same plant (6, 12). That variability matters for this review because it means a pretreatment tuned for one residue is rarely optimal for another, a point that returns in later sections (Figure 1).




Figure 1. From residue to ethanol, with the points where sugar or product is lost (schematic, not data).

The overall process is usually drawn as a short chain. Residue is collected, pretreated, hydrolysed with cellulase and hemicellulase enzymes, fermented and distilled. Two arrangements are common: separate hydrolysis and fermentation, where each step runs under its own best conditions, and simultaneous saccharification and fermentation, where enzymes and microbes share a vessel (13, 14). A more ambitious idea, consolidated bioprocessing, would have a single microbial system produce the enzymes and make the ethanol (15). It remains largely a goal rather than a routine practice.

2.2 Pretreatment Families

Pretreatment is meant to make cellulose accessible, and it does so by removing or rearranging hemicellulose and lignin, or by changing the physical structure of the fibre



(16, 17). The methods fall into a few families, summarised in Table 1. Dilute acid dissolves most of the hemicellulose and has been studied extensively for cereal straws and corn stover (8, 18). Steam explosion uses heat and pressure followed by a sudden release, which disrupts the fibre (19). Ammonia-based methods swell the material and change the lignin without dissolving much of the hemicellulose (20). Alkaline treatments, including lime, act mainly on lignin (21). Organic solvents can separate lignin as a distinct fraction, and biological treatments with fungi are gentle but slow (22, 23).

Table 1. Main pretreatment families for agricultural residues and their usual trade-offs.

Pretreatment	Main effect	Usual drawback
Dilute acid	Solubilises hemicellulose (8, 16)	Inhibitor formation; corrosion (24)
Steam explosion	Opens fibre structure (19)	Sugar degradation; incomplete lignin removal
Ammonia (AFEX, recycle percolation)	Swells fibre, partial lignin change (20, 25)	Ammonia handling and recovery
Alkaline or lime	Removes lignin, spares sugars (21)	Salt handling; long residence times
Organosolv	Separates lignin fraction (17)	Solvent recovery cost
Biological	Gentle, low chemical use (22)	Slow; consumes some carbohydrate

Note: Qualitative summary of tendencies described in the cited reviews; behaviour varies with the residue and the conditions used.

The reviews agree on one point and differ on others. They agree that there is no universally best method; what suits a hardwood does not necessarily suit a straw, and what is cheap in a laboratory may be costly at scale (16, 26). They differ on how

much weight to give to different drawbacks. Some stress inhibitor formation, some emphasise chemical recovery, and some focus on how well the pretreated solid responds to enzymes (19, 23). The tendencies are drawn together in Figure 2, which is a qualitative map and not a ranking. For anyone planning a plant, the useful question is what would survive scale-up.

	Hemicellulose removed	Lignin removed	Inhibitor risk	Chemical recovery
Dilute acid	marked	minor	marked	minor
Steam explosion	marked	minor	partial	minor
Ammonia (AFEX)	minor	partial	minor	marked
Alkaline / lime	partial	marked	minor	partial
Organosolv	marked	marked	partial	marked

qualitative tendencies, not data

Figure 2. Qualitative tendencies of pretreatment families (schematic matrix, not data).

2.3 Hydrolysis and the Problem of Inhibition

Once the fibre is open, cellulases convert the cellulose to glucose. The enzymology is complex, because several activities must work together on a solid substrate whose surface changes as it is consumed (12). Hydrolysis tends to slow as it proceeds, partly because the easily reached cellulose goes first, partly because the products inhibit the enzymes, and partly because lignin binds enzyme unproductively (10, 11). Adding hemicellulose-degrading enzymes can help, since removing xylan exposes more cellulose (27).

Industrial economics push towards high solids loading, since a dilute slurry means large vessels and a dilute product. High solids, however, bring mixing, mass-transfer and inhibition problems of their own (28). The laboratory result obtained at low loading is therefore a poor



guide to what a plant would see. That gap between laboratory and plant is easy to underestimate.

Pretreatment itself can create inhibitors. Acids and heat break sugars down to furfural and hydroxymethylfurfural, release acetic acid from the hemicellulose, and liberate phenolic compounds from lignin (24, 29). These compounds slow or stop fermentation, and their combined effect is not simply the sum of their parts (30). Detoxification steps can remove them but add cost and may remove sugar as well (13, 31). The more severe the pretreatment, the more of the hemicellulose sugar is recovered in some cases and the more is destroyed in others, which is the central tension in the field.

2.4 Organisms for Fermentation

Baker's yeast, *Saccharomyces cerevisiae*, remains the workhorse of ethanol production because it is fast, robust and tolerant of ethanol and low pH (32). Its limitation is that it does not ferment xylose, the second most abundant sugar in straws. Since hemicellulose may account for a substantial share of the fermentable material, leaving the xylose unused sets a ceiling on yield (9, 33). Table 2 lists the main organisms and the trade-offs that come with them.

Two lines of work addressed the problem, and Figure 3 marks some of the milestones. The first modified bacteria, since several can ferment pentoses naturally or with modest changes. *Escherichia coli* was engineered early to make ethanol as its main product (39), and *Zymomonas mobilis*, a natural ethanol producer, was given the ability to use pentoses (37). These bacteria are less tolerant of the conditions in an industrial hydrolysate than yeast, a weakness that reviews return to repeatedly (38). The second line gave yeast a route for xylose, either through a pair of oxidoreductase

enzymes or through isomerase (34, 35). Reviews of the resulting strains describe real progress alongside persistent problems: slower xylose use than glucose use, sensitivity to inhibitors, and the by-products that appear when the redox balance is disturbed (33, 36).

Table 2. Fermenting organisms discussed for residue hydrolysates.

Organism	Strength	Constraint
<i>Saccharomyces cerevisiae</i> (wild type)	Robust, tolerant, industrial history (32)	Does not use xylose naturally (33)
<i>S. cerevisiae</i> (engineered)	Uses glucose and xylose (34, 35)	Slower xylose use; inhibitor sensitivity (36)
<i>Zymomonas mobilis</i> (engineered)	Efficient ethanol formation (37)	Narrow substrate range; tolerance (38)
<i>Escherichia coli</i> (engineered)	Broad sugar range (39)	Lower ethanol tolerance; pH sensitivity (38)

Note: Strengths and constraints are those described in the cited reviews; no performance figures are given because they depend on strain, medium and conditions.




Figure 3. Selected milestones in microbial ethanol from lignocellulose (schematic timeline, not to scale).

A further complication is that glucose and xylose are not used at the same rate. In mixtures, glucose is usually taken up first, and xylose follows slowly, so that



fermentations can run long and leave sugar behind (36). Strains developed for cellulosic ethanol have been demonstrated on real hydrolysates of ammonia-treated corn stover (25), which is encouraging, although a demonstration is not the same as a robust process across different residues.

2.5 Residues in Context: Supply, Land and Cost

Residues are not free. They have to be collected, baled, stored and transported, and they have competing uses as animal feed, bedding and soil cover. Theoretical estimates of potential, such as those made at global scale (3), necessarily assume that much of the residue can be removed and used, an assumption that agronomists question wherever soil organic matter is at stake. The argument for residues also rests on a comparison with crop-based ethanol, whose land-use consequences have been debated at length (1, 2, 40).

3. Materials and Methods

3.1 Scope and Question

The review asks one question in two parts. First, what are the main pretreatment strategies used to prepare agricultural residues for microbial ethanol production, and what do they cost in terms of sugar, inhibitors and process complexity? Second, which constraints, from biology as well as engineering, most plausibly hold final ethanol yield below what the sugar content of the residue would allow? The scope is the biochemical route from lignocellulosic residue to ethanol; thermochemical routes, biogas and other products are outside it.

3.2 Literature Assembly

The review draws on peer-reviewed work in four areas: the structure and chemistry of lignocellulose; the pretreatment and hydrolysis of cereal straws, corn stover and

related residues; fermentation and the engineering of ethanol-producing microbes; and the sustainability and economic literature that frames the debate. Published reviews were used as entry points, and original studies were consulted where a point needed support. Only work published up to the year of this issue is cited.

We did not run a formal systematic search and we do not claim one. This is a narrative synthesis, and the choice of sources reflects the authors' judgement. The practical consequence is that the review is a better guide to the structure of the problem than to the exact weight of evidence for any single method, and it can miss relevant studies that a formal search would find. The point is not that such a review is unreliable, only that its reach has limits.

3.3 Appraisal Framework

To judge how far a report can be trusted, we asked four questions of each source. Was the residue and its composition described? Were pretreatment conditions stated well enough to be repeated? Was yield expressed in a way that can be compared, for example per unit of starting material rather than per unit of sugar released? And were inhibitors, enzyme loading and solids loading reported? These questions, summarised in Table 3 alongside the stages at which yield is lost, shaped how findings are presented below.

4. Results

4.1 What the Literature Says About Pretreatment

Across the reviews, a pattern emerges that is more interesting than a ranking. Methods that solubilise hemicellulose, such as dilute acid, recover pentose sugars early but risk degrading them and forming inhibitors (16, 24). Methods that leave hemicellulose largely in place, such as



ammonia-based treatments, produce less inhibition but rely on enzymes to release the pentoses later (20, 27). Methods that remove lignin make the cellulose more accessible and reduce non-productive enzyme binding, at the price of chemicals that have to be handled and recovered (17, 21).

The residue matters at least as much as the method. Reviews of rice straw and wheat straw describe the same families of pretreatment but point to different difficulties, among them the high ash content of rice straw and the sensitivity of the wheat straw hydrolysate to inhibitors (18, 41). A claim that a method works on one straw cannot safely be carried to another. This is why the same residue can look promising in one laboratory and disappointing in another.

4.2 Sugar Balance and Where Yield Goes

Ethanol yield is the product of several fractions. Not all of the residue is carbohydrate. Of the carbohydrate, only part is recovered after pretreatment, part of that is converted by enzymes, and part of the sugar released is fermented (7, 14). Even a perfect fermentation does not turn all the sugar into ethanol, because a share of the carbon leaves as carbon dioxide and a share goes into cell growth. At best, a little over half the mass of fermented sugar ends up as ethanol.

The consequence is that moderate losses at each stage compound into large ones. A pretreatment that degrades some sugar, a hydrolysis that leaves some cellulose behind and a fermentation that ignores the xylose each look acceptable alone and together remove a large part of the potential (26, 32). Published yields are often reported against only one of the denominators, which makes the whole look better than the parts (42). Such losses look small stage by stage, but they

multiply along the chain.

4.3 The Main Constraints

Table 3 gathers the stages and the common responses. Four constraints recur in the literature. The first is recalcitrance, the physical and chemical resistance of the fibre, which sets the cost of opening it (6, 10). The second is inhibition, from compounds produced in pretreatment and from the sugars and ethanol themselves (29, 30, 31). The third is the incomplete use of pentoses (33, 36). The fourth is the dilution of the product, which raises the energy and capital cost of recovery (28, 43).

Table 3. Where ethanol yield is lost between residue and fuel.

Stage	Source of loss	Common response
Harvest and storage	Residue that is not collected or spoils (3)	Collection logistics
Pretreatment	Sugars degraded, hemicellulose lost (26)	Milder, better-matched conditions
Hydrolysis	Incomplete conversion; enzyme binding to lignin (11, 12)	Enzyme mixtures, supplementary enzymes (27)
Fermentation	Inhibitors; unused pentoses (9, 29)	Detoxification, tolerant strains (44)
Recovery	Dilute product stream (28)	Higher solids loading

Note: The stages are conceptual; the relative size of each loss differs between residues and process designs and is not quantified here.

These constraints interact, which is the main reason they are hard to solve one at a time. A harsher pretreatment lowers recalcitrance and raises inhibition. A higher solids loading eases the burden of recovery and worsens both mixing and inhibition. A tolerant yeast strain can ease the fermentation problem, but if the hydrolysate is changed to suit it, the



enzyme step may suffer (24, 44). A saving that disappears once chemicals, energy and water are counted is not one a plant operator would see.

4.4 Quality and Comparability of the Evidence

The most striking feature of the literature is how difficult it is to compare. Studies use different residues, different particle sizes, different solids and enzyme loadings, different strains and different ways of expressing yield (19, 23). Many are conducted in small batch vessels with defined media or well-washed solids that a plant would not have, and some report the yield of sugar released instead of the ethanol made. Reviews of this kind are more useful when they say where the evidence stops than when they smooth it over.

5. Discussion

5.1 Interpretation

The central finding of this review is that bioethanol from residues is a systems problem. Looking at the literature as a whole, the question is rarely whether a step can be done; it is whether it can be done without making the next step harder. Pretreatment is the best example, because its choice shapes what the enzymes can do, which inhibitors the microbes meet and how much chemical has to be recovered (16, 26).

A second reading concerns the strain engineering. The step from a yeast that cannot use xylose to one that can was an important achievement (34, 35), and it changed the theoretical yield from residues. Yet the same literature shows that strain performance is tied to the hydrolysate, so that progress in biology cannot replace good process design (32, 36).

A third reading is about expectations. Early optimism about residue ethanol tended to rest on the size of the resource and the elegance of the biology (4, 5). Later assessments are more cautious about cost and about the pace of scale-up (42, 45). The cautious reading is not pessimistic, but it asks for better accounting. Three kinds of finding would change the picture: a pretreatment that opens several different residues at low severity and without chemical recovery, a robust strain that ferments real hydrolysates of high solids content at industrial rates, or an enzyme system that tolerates lignin and product inhibition far better than current ones. Read this way, a failure in a single run says little about the method itself.

5.2 Limitations

This is a narrative review and shares the limitations of that form. Source selection reflects the authors' judgement, no formal search or quality scoring was done, and the review does not extract numerical results from individual studies. It may therefore under-represent work from regions and journals that are less visible in the sources that guided it. Readers should weigh the conclusions with that in mind.

5.3 Directions for Future Work

Three needs stand out. The first is common reporting. If studies stated the residue composition, the pretreatment conditions, the solids and enzyme loadings and expressed yield against the starting material, comparison across laboratories would become possible (19, 28). The second is testing of strains and enzymes on realistic, high-solids hydrolysates of several residues, instead of defined sugar mixtures (31, 44). The third is an honest accounting of the residue supply chain, including collection, storage and the effect of removal on soil, so that estimates of potential are matched to what can be used



(3). There is also room for pretreatments designed around the downstream steps instead of in isolation, and for uses of the lignin fraction as a product and not only as a nuisance (5, 17).

6. Conclusion

Agricultural residues are a plausible raw material for microbial ethanol, and the literature describes a workable route from straw to fuel. The route is not a simple one. Pretreatment determines much of what follows, no method is best on every count, and yield is lost at several stages that interact. The engineering of yeasts and bacteria that use xylose has removed one large ceiling, but real hydrolysates still impose tolerance and rate problems that defined sugar mixtures hide.

For the practitioner, the message is to match the pretreatment to the residue and the organism, to measure losses at each stage and to be wary of single-number yields. For the researcher, the opportunity lies in comparable reporting, realistic substrates and joint design of the steps. These cautions apply equally to any lignocellulosic feedstock, not only to cereal straws.

7. Acknowledgements

The authors thank colleagues who commented on earlier drafts of this review.

8. Funding

This work received no specific grant from any funding agency in the public, commercial or not-for-profit sectors.

9. Conflict of Interest

The authors declare no conflict of interest.

10. Author Contributions

E.L. conceived the review and wrote the sections on lignocellulose and pretreatment. D.V. wrote the sections on fermentation and strain engineering. M.E.

wrote the sections on process constraints and economics. All authors reviewed and approved the final manuscript.

11. Ethics Statement

This is a review of published literature. No human participants or animals were involved and no ethical approval was required.

12. Data Availability

No new data were generated. All sources are cited in the reference list.

13. References

1. Searchinger, T., Heimlich, R., Houghton, R. A., Dong, F., Elobeid, A., Fabiosa, J., ... Yu, T.-H. (2008). Use of U.S. croplands for biofuels increases greenhouse gases through emissions from land-use change. *Science*, 319(5867), 1238–1240. DOI: [10.1126/science.1151861](https://doi.org/10.1126/science.1151861)
2. Fargione, J., Hill, J., Tilman, D., Polasky, S., & Hawthorne, P. (2008). Land clearing and the biofuel carbon debt. *Science*, 319(5867), 1235–1238. DOI: [10.1126/science.1152747](https://doi.org/10.1126/science.1152747)
3. Kim, S., & Dale, B. E. (2004). Global potential bioethanol production from wasted crops and crop residues. *Biomass and Bioenergy*, 26(4), 361–375. DOI: [10.1016/j.biombioe.2003.08.002](https://doi.org/10.1016/j.biombioe.2003.08.002)
4. Farrell, A. E., Plevin, R. J., Turner, B. T., Jones, A. D., O'Hare, M., & Kammen, D. M. (2006). Ethanol can contribute to energy and environmental goals. *Science*, 311(5760), 506–508. DOI: [10.1126/science.1121416](https://doi.org/10.1126/science.1121416)
5. Ragauskas, A. J., Williams, C. K., Davison, B. H., Britovsek, G., Cairney, J., Eckert, C. A., ... Tschaplinski, T. (2006). The path forward for biofuels and biomaterials. *Science*, 311(5760), 484–489. DOI: [10.1126/science.1114736](https://doi.org/10.1126/science.1114736)
6. Himmel, M. E., Ding, S.-Y., Johnson, D. K., Adney, W. S., Nimlos, M. R., Brady, J. W., & Foust, T. D. (2007). Biomass recalcitrance: Engineering plants and enzymes for biofuels production. *Science*, 315(5813), 804–807. DOI: [10.1126/science.1137016](https://doi.org/10.1126/science.1137016)
7. Balat, M. (2011). Production of bioethanol from lignocellulosic materials via the biochemical pathway: A review. *Energy Conversion and Management*, 52(2), 858–875. DOI: [10.1016/j.enconman.2010.08.013](https://doi.org/10.1016/j.enconman.2010.08.013)
8. Sun, Y., & Cheng, J. (2002). Hydrolysis of lignocellulosic materials for ethanol production: A review. *Bioresource Technology*, 83(1), 1–11. DOI: [10.1016/S0960-8524\(01\)00212-7](https://doi.org/10.1016/S0960-8524(01)00212-7)



9. Gírio, F. M., Fonseca, C., Carvalheiro, F., Duarte, L. C., Marques, S., & Bogel-Lukasik, R. (2010). Hemicelluloses for fuel ethanol: A review. *Bioresource Technology*, 101(13), 4775–4800. DOI: [10.1016/j.biortech.2010.01.088](https://doi.org/10.1016/j.biortech.2010.01.088)
10. Chundawat, S. P. S., Beckham, G. T., Himmel, M. E., & Dale, B. E. (2011). Deconstruction of lignocellulosic biomass to fuels and chemicals. *Annual Review of Chemical and Biomolecular Engineering*, 2, 121–145. DOI: [10.1146/annurev-chembioeng-061010-114205](https://doi.org/10.1146/annurev-chembioeng-061010-114205)
11. Berlin, A., Balakshin, M., Gilkes, N., Kadla, J., Maximenko, V., Kubo, S., & Saddler, J. (2006). Inhibition of cellulase, xylanase and β -glucosidase activities by softwood lignin preparations. *Journal of Biotechnology*, 125(2), 198–209. DOI: [10.1016/j.jbiotec.2006.02.021](https://doi.org/10.1016/j.jbiotec.2006.02.021)
12. Zhang, Y.-H. P., & Lynd, L. R. (2004). Toward an aggregated understanding of enzymatic hydrolysis of cellulose: Noncomplexed cellulase systems. *Biotechnology and Bioengineering*, 88(7), 797–824. DOI: [10.1002/bit.20282](https://doi.org/10.1002/bit.20282)
13. Olsson, L., & Hahn-Hägerdal, B. (1996). Fermentation of lignocellulosic hydrolysates for ethanol production. *Enzyme and Microbial Technology*, 18(5), 312–331. DOI: [10.1016/0141-0229\(95\)00157-3](https://doi.org/10.1016/0141-0229(95)00157-3)
14. Sánchez, Ó. J., & Cardona, C. A. (2008). Trends in biotechnological production of fuel ethanol from different feedstocks. *Bioresource Technology*, 99(13), 5270–5295. DOI: [10.1016/j.biortech.2007.11.013](https://doi.org/10.1016/j.biortech.2007.11.013)
15. Lynd, L. R., Weimer, P. J., van Zyl, W. H., & Pretorius, I. S. (2002). Microbial cellulose utilization: Fundamentals and biotechnology. *Microbiology and Molecular Biology Reviews*, 66(3), 506–577. DOI: [10.1128/MMBR.66.3.506-577.2002](https://doi.org/10.1128/MMBR.66.3.506-577.2002)
16. Mosier, N., Wyman, C., Dale, B., Elander, R., Lee, Y. Y., Holtzapple, M., & Ladisch, M. (2005). Features of promising technologies for pretreatment of lignocellulosic biomass. *Bioresource Technology*, 96(6), 673–686. DOI: [10.1016/j.biortech.2004.06.025](https://doi.org/10.1016/j.biortech.2004.06.025)
17. Hu, F., & Ragauskas, A. (2012). Pretreatment and lignocellulosic chemistry. *BioEnergy Research*, 5(4), 1043–1066. DOI: [10.1007/s12155-012-9208-0](https://doi.org/10.1007/s12155-012-9208-0)
18. Talebnia, F., Karakashev, D., & Angelidaki, I. (2010). Production of bioethanol from wheat straw: An overview on pretreatment, hydrolysis and fermentation. *Bioresource Technology*, 101(13), 4744–4753. DOI: [10.1016/j.biortech.2009.11.080](https://doi.org/10.1016/j.biortech.2009.11.080)
19. Alvira, P., Tomás-Pejó, E., Ballesteros, M., & Negro, M. J. (2010). Pretreatment technologies for an efficient bioethanol production process based on enzymatic hydrolysis: A review. *Bioresource Technology*, 101(13), 4851–4861. DOI: [10.1016/j.biortech.2009.11.093](https://doi.org/10.1016/j.biortech.2009.11.093)
20. Kim, T. H., & Lee, Y. Y. (2005). Pretreatment and fractionation of corn stover by ammonia recycle percolation process. *Bioresource Technology*, 96(18), 2007–2013. DOI: [10.1016/j.biortech.2005.01.015](https://doi.org/10.1016/j.biortech.2005.01.015)
21. Kumar, P., Barrett, D. M., Delwiche, M. J., & Stroeve, P. (2009). Methods for pretreatment of lignocellulosic biomass for efficient hydrolysis and biofuel production. *Industrial & Engineering Chemistry Research*, 48(8), 3713–3729. DOI: [10.1021/ie801542g](https://doi.org/10.1021/ie801542g)
22. Hendriks, A. T. W. M., & Zeeman, G. (2009). Pretreatments to enhance the digestibility of lignocellulosic biomass. *Bioresource Technology*, 100(1), 10–18. DOI: [10.1016/j.biortech.2008.05.027](https://doi.org/10.1016/j.biortech.2008.05.027)
23. Taherzadeh, M. J., & Karimi, K. (2008). Pretreatment of lignocellulosic wastes to improve ethanol and biogas production: A review. *International Journal of Molecular Sciences*, 9(9), 1621–1651. DOI: [10.3390/ijms9091621](https://doi.org/10.3390/ijms9091621)
24. Larsson, S., Palmqvist, E., Hahn-Hägerdal, B., Tengborg, C., Stenberg, K., Zacchi, G., & Nilvebrant, N.-O. (1999). The generation of fermentation inhibitors during dilute acid hydrolysis of softwood. *Enzyme and Microbial Technology*, 24(3–4), 151–159. DOI: [10.1016/S0141-0229\(98\)00101-X](https://doi.org/10.1016/S0141-0229(98)00101-X)
25. Lau, M. W., & Dale, B. E. (2009). Cellulosic ethanol production from AFEX-treated corn stover using *Saccharomyces cerevisiae* 424A(LNH-ST). *Proceedings of the National Academy of Sciences*, 106(5), 1368–1373. DOI: [10.1073/pnas.0812364106](https://doi.org/10.1073/pnas.0812364106)
26. Galbe, M., & Zacchi, G. (2007). Pretreatment of lignocellulosic materials for efficient bioethanol production. *Advances in Biochemical Engineering/Biotechnology*, 108, 41–65. DOI: [10.1007/10_2007_070](https://doi.org/10.1007/10_2007_070)
27. Kumar, R., & Wyman, C. E. (2009). Effects of cellulase and xylanase enzymes on the deconstruction of solids from pretreatment of poplar by leading technologies. *Biotechnology Progress*, 25(2), 302–314. DOI: [10.1002/btpr.102](https://doi.org/10.1002/btpr.102)
28. Modenbach, A. A., & Nokes, S. E. (2013). Enzymatic hydrolysis of biomass at high-solids loadings – a review. *Biomass and Bioenergy*, 56, 526–544. DOI: [10.1016/j.biombioe.2013.05.031](https://doi.org/10.1016/j.biombioe.2013.05.031)
29. Palmqvist, E., & Hahn-Hägerdal, B. (2000). Fermentation of lignocellulosic hydrolysates. II: Inhibitors and mechanisms of inhibition. *Bioresource Technology*, 74(1), 25–33. DOI: [10.1016/S0960-8524\(99\)00161-3](https://doi.org/10.1016/S0960-8524(99)00161-3)
30. Palmqvist, E., & Hahn-Hägerdal, B. (2000). Fermentation of lignocellulosic hydrolysates. I: Inhibition and detoxification. *Bioresource*



- Technology*, 74(1), 17–24. DOI: [10.1016/S0960-8524\(99\)00160-1](https://doi.org/10.1016/S0960-8524(99)00160-1)
31. Jönsson, L. J., & Martín, C. (2016). Pretreatment of lignocellulose: Formation of inhibitory by-products and strategies for minimizing their effects. *Bioresource Technology*, 199, 103–112. DOI: [10.1016/j.biortech.2015.10.009](https://doi.org/10.1016/j.biortech.2015.10.009)
 32. Hahn-Hägerdal, B., Galbe, M., Gorwa-Grauslund, M. F., Lidén, G., & Zacchi, G. (2006). Bio-ethanol – the fuel of tomorrow from the residues of today. *Trends in Biotechnology*, 24(12), 549–556. DOI: [10.1016/j.tibtech.2006.10.004](https://doi.org/10.1016/j.tibtech.2006.10.004)
 33. Jeffries, T. W. (2006). Engineering yeasts for xylose metabolism. *Current Opinion in Biotechnology*, 17(3), 320–326. DOI: [10.1016/j.copbio.2006.05.008](https://doi.org/10.1016/j.copbio.2006.05.008)
 34. Ho, N. W. Y., Chen, Z., & Brainard, A. P. (1998). Genetically engineered *Saccharomyces* yeast capable of effective cofermentation of glucose and xylose. *Applied and Environmental Microbiology*, 64(5), 1852–1859. DOI: [10.1128/AEM.64.5.1852-1859.1998](https://doi.org/10.1128/AEM.64.5.1852-1859.1998)
 35. Kuyper, M., Winkler, A. A., van Dijken, J. P., & Pronk, J. T. (2004). Minimal metabolic engineering of *Saccharomyces cerevisiae* for efficient anaerobic xylose fermentation: A proof of principle. *FEMS Yeast Research*, 4(6), 655–664. DOI: [10.1016/j.femsyr.2004.01.003](https://doi.org/10.1016/j.femsyr.2004.01.003)
 36. Hahn-Hägerdal, B., Karhumaa, K., Fonseca, C., Spencer-Martins, I., & Gorwa-Grauslund, M. F. (2007). Towards industrial pentose-fermenting yeast strains. *Applied Microbiology and Biotechnology*, 74(5), 937–953. DOI: [10.1007/s00253-006-0827-2](https://doi.org/10.1007/s00253-006-0827-2)
 37. Zhang, M., Eddy, C., Deanda, K., Finkelstein, M., & Picataggio, S. (1995). Metabolic engineering of a pentose metabolism pathway in ethanologenic *Zymomonas mobilis*. *Science*, 267(5195), 240–243. DOI: [10.1126/science.267.5195.240](https://doi.org/10.1126/science.267.5195.240)
 38. Dien, B. S., Cotta, M. A., & Jeffries, T. W. (2003). Bacteria engineered for fuel ethanol production: Current status. *Applied Microbiology and Biotechnology*, 63(3), 258–266. DOI: [10.1007/s00253-003-1444-y](https://doi.org/10.1007/s00253-003-1444-y)
 39. Ingram, L. O., Conway, T., Clark, D. P., Sewell, G. W., & Preston, J. F. (1987). Genetic engineering of ethanol production in *Escherichia coli*. *Applied and Environmental Microbiology*, 53(10), 2420–2425. DOI: [10.1128/aem.53.10.2420-2425.1987](https://doi.org/10.1128/aem.53.10.2420-2425.1987)
 40. Tilman, D., Socolow, R., Foley, J. A., Hill, J., Larson, E., Lynd, L., ... Williams, R. (2009). Beneficial biofuels – the food, energy, and environment trilemma. *Science*, 325(5938), 270–271. DOI: [10.1126/science.1177970](https://doi.org/10.1126/science.1177970)
 41. Binod, P., Sindhu, R., Singhania, R. R., Vikram, S., Devi, L., Nagalakshmi, S., ... Pandey, A. (2010). Bioethanol production from rice straw: An overview. *Bioresource Technology*, 101(13), 4767–4774. DOI: [10.1016/j.biortech.2009.10.079](https://doi.org/10.1016/j.biortech.2009.10.079)
 42. Wyman, C. E. (2007). What is (and is not) vital to advancing cellulosic ethanol. *Trends in Biotechnology*, 25(4), 153–157. DOI: [10.1016/j.tibtech.2007.02.009](https://doi.org/10.1016/j.tibtech.2007.02.009)
 43. Hamelinck, C. N., van Hooijdonk, G., & Faaij, A. P. C. (2005). Ethanol from lignocellulosic biomass: Techno-economic performance in short-, middle- and long-term. *Biomass and Bioenergy*, 28(4), 384–410. DOI: [10.1016/j.biombioe.2004.09.002](https://doi.org/10.1016/j.biombioe.2004.09.002)
 44. Almeida, J. R. M., Modig, T., Petersson, A., Hahn-Hägerdal, B., Lidén, G., & Gorwa-Grauslund, M. F. (2007). Increased tolerance and conversion of inhibitors in lignocellulosic hydrolysates by *Saccharomyces cerevisiae*. *Journal of Chemical Technology and Biotechnology*, 82(4), 340–349. DOI: [10.1002/jctb.1676](https://doi.org/10.1002/jctb.1676)
 45. Lynd, L. R., Laser, M. S., Bransby, D., Dale, B. E., Davison, B., Hamilton, R., ... Wyman, C. E. (2008). How biotech can transform biofuels. *Nature Biotechnology*, 26(2), 169–172. DOI: [10.1038/nbt0208-169](https://doi.org/10.1038/nbt0208-169)